



IRE 250 C1



- Insulated duct fan with circular connections.
- Equipped with 50 mm of thermal and acoustic insulation makes it ideal for handling cold air.
- Designed for high pressure and long, complicated duct runs.
- The design prioritise functionality, durability and longevity.
- Impeller with forward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings.
- Integrated motor protection.
- Junction box has enclosure class IP 54.
- For speed control a transformer or electronic speed controller can be connected.
- The housing is manufactured from galvanized sheet steel.
- Duct connections are equipped with rubber seals.
- The fan is intended to be installed in a duct system.
- A duct connected fan can be installed outside or in damp environments.
- To comply with the ErP 2018 regulation, a local demand controller must be used.



DIAGRAMS



Data

Air Flow (l/s)	External static pressure (Pa)	Power (W)	Speed (r.p.m.)	Current (A)	Voltage (V)
152	317	172	2588	0.761	230

DIAGRAMS




DATA

Efficiency (%)
28

SFP (kW/m³/s)
1.13

SOUND DATA



	Tot	63	125	250	500	1k	2k	4k	8k
Inlet Lw dB(A)	63	52	59	58	55	50	47	46	44
Outlet Lw dB(A)	70	57	61	60	63	62	63	61	58
Surrounding Lw dB(A)	49	39	38	45	39	34	36	35	37
Surrounding Lp dB (A) 20m ² Sabine, hemispherical 3m	42								

Data - SOUND

Air Flow (l/s)	External static pressure (Pa)	Power (W)	Speed (r.p.m.)	Current (A)	Efficiency (%)	SFP (kW/m ³ /s)	Voltage (V)
152	317	172	2588	0.761	28	1.13	230

TECHNICAL DATA

Parameter	IRE 250 C1 man tp 7900019		IRE 250 C1 aut tp 7900095	
	Value	Unit	Value	Unit
Voltage	230	V	230	V
Phase	1	~	1	~
Frequency	50	Hz	50	Hz
Power	256	W	256	W
Current	1.13	A	1.13	A
Speed	2120	r.p.m.	2120	r.p.m.
Max. temperature of transported air	50	°C	50	°C
Max. temperature of transported air when speed controlled	50	°C	50	°C
Sound pressure level at 3 m	42	dB(A)	42	dB(A)
Weight	14.4	kg	14.4	kg
Enclosure class	44	IP	44	IP
Insulation class, motor	F		F	
Capacitor	5	µF	5	µF
Duct connection	250	mm	250	mm
Max. flow @ 0Pa	275	l/s	275	l/s
Max. pressure	442	Pa	442	Pa
Voltage range	220-240	V	220-240	V


PRODUCT INFORMATION SHEET

Parameter	Value	Unit
(a) Manufacturer	Östberg	-
(b) Model code	IRE 250 C1	-
(c) SEC average climate	-23.9	kWh/m ²
SEC average climate, class	C	-
SEC warm climate	-8.4	kWh/m ²
SEC warm climate, class	F	-
SEC cold climate	-51	kWh/m ²
SEC cold climate, class	A+	-
(d) Declared type	RVU / UVU	-
(e) Type of drive	Multi-speed drive (accessory)	-
(f) Type of heat recovery	None	-
(g) Thermal efficiency	None	%
(h) Max. flow rate (@100Pa)	932	m ³ /h
(i) Power at max. flow rate	246	W
(j) Sound power level	47	dB LwA
(k) Reference flow rate	0.275	m ³ /s
(l) Reference pressure difference	50	Pa
(m) SPI	0.27	W/(m ³ /h)
(n) Type of control/ctrl factor	Local demand control(accessory)/0.65	-
(o) External (and internal) leakage rate	0.38 (N/A)	%
(p) Mixing rate	N/A	-
(q) Visual filter warning	N/A	-
(r) Instruction supply/exhaust grilles	See manual	-
(s) Disassembly instructions	fsp.ostberg.com	-
(t) Airflow sensitivity	N/A	-
(u) Air tightness	N/A	m/s
(v) AEC	175	kWh

Parameter	Value	Unit
(w) AHS average	2830	kWh
AHS warmer	1280	kWh
AHS colder	5536	kWh

WIRING DIAGRAM

4040001



(M) = Fan Motor

(M1) = Fan Motor

(M2) = Fan Motor

(M3) = Rotor Motor

1 = Yellow/Green

2 = Black

3 = Blue

4 = Brown

5 = White

6 = Orange

7 = Grey

8 = Red


9 = Green

10 = Violet

11 = Quick switch

12 = Yellow

DIMENSIONS



ACCESSORIES

Mechanical accessories



Mounting bracket Kit
Universal



Mounting clamp MK
250



Safety grille BSV 250



Back draught shutter
RSK 250



Louvre YG 250



Louvre shutter VK
250



Filterbox FLK 250



Filterbox FLF 250



Silencer LDC 250

Electrical accessories



Transformer
controller VRTE 1



Transformer
controller VRDE 1.5



Speed controller VRS
2.0



Local Demand
Controller Kit