

DTV250 roof fan, vertical exhaust









www.exhausto.com

EXHAUSTO

Technical data, DTV250-4-1EC

DTV250-4-1EC

MODEL	DTV250-4-1EC
Fan data	
Max. overall efficiency	51,9 %
ECO measurement set-up (A-D)	C
Efficiency requirements	62, N(2015)
ECO efficiency at optimal operating point	76,2
Motor	
Motor	EC motor with integral VSD
Optimal operating point: Absorbed power Airflow Total pressure Rpm	159 W 1111 m ^{3/} h 268 Pa 1635 rpm
Nominal rpm (N)	1635 rpm
Electric supply (U)	1 x 230 V ~ 50 Hz
Overload protection	Integrated in motor control
Max absorbed current* (I)	1.2 A
Max. absorbed power (P ₁)**	0.11 kW
Motor output (P ₂)**	0,16 kW
Supply	
Supply (power cable)	-
Length	-
Other data	
Weight	28 kg


Conditions:

- * I is the maximum absorbed current throughout the control range or the full load current if this is larger
- ** P₁ is the maximum absorbed power from the mains supply, where P₂ is the motor's nominal output.
- Stated data are for t = 20°C
- Density = 1.2 kg/m³
- Gas temperature: min. -12°C, max. +60° C
- Ambient temperature: Max +40° C
- Pressure ratio: < 1,11
- other points in acc. with EC327/2011 see product instructions

Capacity diagrams


DTV250

DTV250-4-1EC




Dimensional drawing

DTV250



Sound data

DTV250



	K _[dB(A)]		$\kappa_{ m w[dB]}$						
	K _{wA}	KρA	125	250	500	1 k	2 k	4 k	8 k
					Hz	Hz	Hz	Hz	Hz
L _{w1}			10	3	-2	-8	-12	-20	-26
L _{w3}	3		0	3	1	-1	-5	-17	-21
L_{pA3}		-25							

EXHAUSTO

Your ventilation expert and professional business partner

At EXHAUSTO we never compromise on quality, and since we are experts in ventilation with many years of specialised experience, you can be assured of not just the best ventilation solution but also a competent business partner.

EXHAUSTO develops and manufactures high-quality products and systems for comfort ventilation in all areas of use – from offices, shops, schools and institutions to industrial buildings, hotels and hospitals. With a focus on high efficiency ratings and an energy consumption which sets new industry standards, EXHAUSTO is one of the absolute leaders of the field.



Our homes are becoming steadily more airtight. This is a result of striving to bring down energy consumption. But what is good for energy consumption may be bad for indoor climate. Airtight construction makes it hard to evacuate humidity, and humidity provides good growth conditions for mould. Mould not only damages the actual building, but also leads to an unhealthy indoor climate which affects our health and well-being.



WORKING OFFICE VENTILATION

Did you know that studies have shown that a poor indoor climate can affect your employees' productivity by as much as 15%? And that the number of errors made goes up as temperatures rise above 20-22°C or CO, levels top 1000 ppm?



LEARNING SCHOOL VENTILATION

In less than an hour, schoolchildren hit the CO_2 wall. They become tired, get head-aches and lack concentration. A poor indoor climate impairs the teacher's working conditions and drastically reduces pupils' ability to learn.

www.exhausto.com

EXHAUSTO ExportOdensevej 76
DK-5550 Langeskov

Tel. +45 65 66 12 36 export@exhausto.dk www.exhausto.com

